



15 times faster than conventional ovens.

### Heavy Volume | Combination Cooking

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times 866-426-2621.



## High Speed Combination Oven Menumaster<sup>®</sup> Commercial MXP22QT

### Power Output

- Forced convection:
  - 2000 W
  - 200° - 520° F (95° - 270° C) temperature range
  - Forced convected air for enhanced toasting and browning
- Microwave:
  - 2200 W
  - Heats quickly, reduces cooking time
- Infra-red radiant:
  - 3000 W
  - Enhances toasting and browning



### Cuts Costs

- No need for costly ventilation hood - catalytic converter filters grease and odors from the air. Integrated recirculating catalytic converter.
- Uses less energy than a conventional oven.
- Eliminates need for pre-cooking and holding.
- Uses standard metal trays, pans and screens.

### Simplifies Cooking

- Touch pad operation for consistent results.
- Controls are intuitive and simple to use.
- Stores up to 360 menu items.
- Four stage cooking option.
- USB Port compatible with standard flash drives, updates programming in seconds.

- 1.38 cubic ft. (39 liter) oven capacity.
- Door drops down below oven rack providing full access to oven interior.


### Easy to Use and Maintain

- Stainless steel exterior and interior.
- Infra-red elements tilt-up for cleaning.
- Two removable air filters protect oven components.
- 1 year parts, labor, & travel or exchange. 3 years magnetron part.

- Backed by the ACP, Inc. 24/7 ComServ

Support Center, 866-426-2621.


- ETL Listed.



Patents Pending



# MenuMaster® Commercial MXP22QT | High Speed Combination Oven



Drawings available from KCL CADlog - techs@kclcad.com

Specification #:

Specifications	
Model	MXP22QT      UPC Code 728028129403
Cooking Power*	2000W      2200W      3000W
	Forced      Microwave      Infra-red radiant
	Convection
Configuration	Countertop
Programmable Control Pads	10
Total Programmable Settings	360
Power Levels	11
Max. Cooking Time	60:00
Program Menu	Multi-level menu capability
Defrost	Yes, microwave only, power level 2
Time Entry Option	Yes
Microwave Distribution	Double side oscillating antenna
Magnetrons	2
Display	VFD
Stackable	Yes
Stage Cooking	Yes, 4
Door Opening	Pull down, ergonomic handle
Automatic Voltage Sensor	Yes
USB Port	Yes
Temperature Range	200° - 520° F (95° - 270° C)
Air Filter	2 removable, with clean filter reminder
Fan Speed	0-100%
Rack	1 rack position, removable
Exterior Dimensions	H 20 3/8" (518)    W 25 1/8" (638)    D** 27 1/2" (699)
Cavity Dimensions	H 10" (254)    W 16" (406)    D 15" (381)
Door Depth	37 5/8" (956), drop down door
Usable Cavity Space	1.38 cubic ft. (39 liter)
Exterior Finish	Stainless steel
Interior Finish	Stainless steel
Power Consumption	5700 W, 27.4A
Power Output*	2200 W* Microwave
Power Source	208 - 240 V, 60 Hz, 30 A single phase
Plug Configuration / Cord	NEMA 6-30    5 ft. (1.5 m)
Frequency	2450 MHz
Product Weight	150 lbs. (68 kg.)
Ship weight (approx.)	175 lbs. (79 kg.)
Shipping Carton Size	H 34 3/4" (883)    W 28 1/4" (717)    D 32 1/2" (826)

## Specifications

Oven shall combine three cooking modes: forced convection, microwave and infra-red radiant for high speed cooking. Icon operated control panel shall be programmable with the ability to program up to 360 menu items and shall have multi-level menu capability. Programs shall be automatically updated using a USB port that is compatible with standard USB flash drives. Display shall be VFD. There shall be 11 power levels, 4 cooking stages and defrost mode. Microwave output shall be 2200 watts and distributed from two magnetrons located on each side of the cavity. An automatic voltage sensor shall accommodate both 208 and 240 volts. Oven shall provide a temperature range from 200° - 520° F (95° - 270° C) in 5° increments. The convection fan shall distribute the heat throughout the cavity to further reduce cook times. Fan speed can be programmed from 0 to 100% for menu flexibility. The infra-red radiant shall have 3000 watt output and deliver heat from the bottom of the oven. This element shall be hinged for easy cleaning of the oven floor. The oven cavity shall have a 1.38 cubic ft. (39 liter) capacity and use standard metal cookware. Maximum microwave cooking time shall be 60 minutes. Oven shall have a stainless steel exterior and be stackable. Oven cavity shall be stainless steel construction with stainless oven door. Drop down door shall open below oven rack for full access to the cavity. The two side air filters shall be removable for easy cleaning and have a "clean filter" reminder feature. A removable, one position rack shall be included. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, ETL listed for safety and sanitation.

### Included Accessories

- ST10X Pizza Stone

### Optional Accessories

- LG10 Leg Kit

### Warranty

Year 1 - parts, labor, and travel or exchange  
 Years 2 - 3 - magnetron tube (part only) is covered.

### Service

All products are backed by the ACP, Inc.  
 24/7 ComServ Support Center.

AIA File #:

Measurements in ( ) are millimeters

\* IEC 60705 Tested

\*\* Includes handle

